SAFETY DATA SHEET

UV CLEAR COAT

Infosafe No.: LQBYM
ISSUED Date : 02/02/2024
ISSUED by: INVISION SALES PTY LTD

Section 1 - Identification

Product Identifier
UV CLEAR COAT

Company Name
INVISION SALES PTY LTD (ABN 54 101 140 550)

Address
19 Concorde Drive Keilor Park
VIC 3042 Australia

Telephone/Fax Number
Tel: 03 93362066
Fax: 03 93362566

Emergency Phone Number
03 9336 2066 (9 am to 5 pm - Monday to Friday)

Emergency Contact Name
Graeme Funnell

E-mail Address
enquiries@invisionsales.com

Recommended use of the chemical and restrictions on use
Wipe-on coating for automotive headlight lenses and other plastic surfaces.

Other Information
Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Invision Sales makes no representations as to the completeness or accuracy thereof. Information is supplied on the conditions that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Invision Sales or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture
Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.
Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Flammable liquids: Category 3
Acute toxicity: Category 4 - Oral
Acute toxicity: Category 4 - Inhalation
Skin corrosion/irritation: Category 2
Eye damage/irritation: Category 2A
Specific target organ toxicity (single exposure): Category 3 (Narcotic)
Specific target organ toxicity (repeated exposure): Category 2
Aspiration hazard: Category 1
Hazardous to the Aquatic Environment - Acute Hazard: Category 1
Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2

Signal Word (s)
DANGER

Hazard Statement (s)
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)
Flame,Exclamation mark,Health hazard,Environment



Precautionary Statement – Prevention
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash slin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary Statement – Response
P314 Get medical advice/attention if you feel unwell.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor
P331 Do NOT induce vomiting.
P330 Rinse mouth.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use dry powder, foam, carbon dioxide, water mist or water fog to extinguish.
P391 Collect spillage.

Precautionary Statement – Storage
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary Statement – Disposal
P501 Dispose of contents/container to an approved waste disposal plant.

Other Information
This product contains an Ototoxic substance.
Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 3 - Composition and Information on Ingredients

Ingredients

Name	CAS	Proportion
Stoddard solvent	8052-41-3	30-60 %
Distillates (petroleum), hydrotreated light	64742-47-8	10-30 %
Nonane	111-84-2	<10 %
Xylene	1330-20-7	<10 %
Hexanoic acid, 2-ethyl-, manganese salt	15956-58-8	<10 %
Proprietary Resin/Diluent Mixture		Balance

Other Information

Trace components: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitisers).

Section 4 - First Aid Measures

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

Use dry powder, foam, carbon dioxide, water mist or water fog.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific hazards arising from the chemical

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Special Protective Equipment and Precautions for Firefighters

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

Hazchem Code

•3Y

Decomposition Temperature
Not available

Section 6 - Accidental Release Measures

Emergency Procedures
Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

Section 7 - Handling and Storage

Precautions for Safe Handling
Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities
Store in a cool, dry, well-ventilated area away from sources of ignition, foodstuffs, clothing and incompatible materials such as oxidising agents. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.
For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values
WORKPLACE EXPOSURE LIMITS (WEL) November 2026
No exposure value assigned for this material. However, the available exposure limits for ingredients are listed below:

Manganese fume, dust and compounds (as Mn) (inhalable)
TWA: 0.1 mg/m³
Advisory notation: OTO

Manganese fume, dust and compounds (as Mn) (respirable)
TWA: 0.02 mg/m³
Advisory notation: OTO

Nonane
TWA: 200 ppm
TWA: 1050 mg/m³

Oil mist, refined mineral
TWA: 5 mg/m³

Stoddard solvent
TWA: 50 ppm
STEL: 100 ppm

TWA: 296 mg/m³
STEL: 593 mg/m³
Advisory notation: OTO

Xylene (o-, m-, p- isomers)
TWA: 80 ppm
STEL: 150 ppm

TWA: 350 mg/m³
STEL: 655 mg/m³
Advisory notation: OTO
Note/s: (e)

Notes Key:
(e) Workers exposed to this chemical may require specific health monitoring (see regulations 368-378, Schedule 14 to the model WHS Regulations).

Definitions:
TWA (Time Weighted Average): The TWA is the maximum average concentration of an airborne contaminant calculated for an eight-hour working day, based on a 5-day working week (40 hours). A worker must not be exposed to a level above the TWA over the course of an 8-hour working day.

STEL (Short Term Exposure Limit): A STEL is the time weighted average maximum concentration of an airborne contaminant calculated over a 15 minute period. It is intended to protect most workers from the acute effects of exposure.

OTO: Ototoxic. Exposure can increase the risk of hearing loss.
Hearing loss is more likely to occur if a worker is exposed to both noise and ototoxic substances than if exposed to just noise or the ototoxic substance alone. Refer to the Model Code of Practice: Managing noise and preventing hearing loss at work.

Source: Safe Work Australia - WORKPLACE EXPOSURE LIMITS - FOR AIRBORNE CONTAMINANTS - November 2026

Biological Monitoring
Name: Xylene
Determinant: Methylhippuric acids in urine
Value: 1.5 g/g creatinine
Sampling time: End of shift
Source: American Conference of Industrial Hygienists (ACGIH).

Control Banding
Not available

Engineering Controls
This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.
Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection
If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.
Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection
Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.
Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection
Wear gloves of impervious material such as latex, neoprene, nitrile or vinyl. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.
Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Thermal Hazards
No further relevant information available.

Body Protection
Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Section 9 - Physical and Chemical Properties

Properties	Description	Properties	Description
Form	Liquid	**Appearance**	Gold Colored Liquid
Colour	Gold	**Odour**	Petroleum/Ether-like
Melting/Freezing Point	Not available	**Boiling Point**	126 - 213 °C
Decomposition Temperature	Not available	**Solubility in Water**	Not soluble
Specific Gravity	Not available	**pH**	Not available
Vapour Pressure	Not available	**Relative Vapour Density (Air=1)**	Heavier than air, 4 - 5.11 mmHg
Evaporation Rate	Not available	**Odour Threshold**	Not available
Viscosity	Not available	**Volatile Component**	VOC weight <60%
Partition Coefficient: n-octanol/water (log value)	Not available	**Flash Point**	43 °C
Flammability	Flammable liquid and vapour	**Auto-Ignition Temperature**	204 - 270 °C
Flammable Limits - Lower	Not available	**Flammable Limits - Upper**	Not available
Explosion Properties	Not available	**Oxidising Properties**	Not available
Particle Characteristics	Not available		

Section 10 - Stability and Reactivity

Reactivity
Reacts with incompatible materials.

Chemical Stability
Stable under normal conditions of storage and handling.

Possibility of hazardous reactions
Reacts with incompatible materials.

Conditions to Avoid
Heat, open flames and other sources of ignition.

Incompatible Materials
Oxidizers, strong acids or bases, reducing agents and aluminum.

Hazardous Decomposition Products
Thermal decomposition giving flammable and toxic products: Carbon
oxides, Hazardous organic compounds, Aldehydes, Ketones, Organic acids, Hydrocarbons.

Hazardous Polymerization
Will not occur.

Section 11 - Toxicological Information

Toxicology Information
No toxicity data available for this material. The available acute toxicity data for the ingredient/s is/are given below.

Acute Toxicity - Oral
Proprietary Resin/Diluent Mixture
>5000 mg/kg

Petroleum distillates/Naphtha
>5000 mg/kg

Xylene
LD50: 3523 mg/kg

Nonane
LD0: >5000 mg/kg

Acute Toxicity - Dermal
Proprietary Resin/Diluent Mixture
>5000 mg/kg

Xylene
1100 mg/kg

Nonane
LD0: >2000 mg/kg

Acute Toxicity - Inhalation
Proprietary Resin/Diluent Mixture
24.83 mg/l/4h (vapour)

Xylene
11 mg/l/4h (vapour)

Nonane
LC50: 17 mg/l/4h (vapour)

Ingestion
Harmful if swallowed. Ingestion of this product may cause irritation to the mouth, throat, oesophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.
May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Inhalation
Harmful if inhaled. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system.
May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Skin
Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Petroleum distillates/Naphtha:
Species: Rabbit
Exposure time: 4h
Method: OECD Test Guideline 404
Result: Irritating to skin.

Xylene:
Causes skin irritation (rabbit)

Nonane:
Causes skin irritation (rabbit)
Irritation Index: 2.9/8 (4 h)

Eye
Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Xylene:
Causes mild eye irritation. (rabbit) (data for a similar material)

Nonane:
Causes mild eye irritation. (rabbit) (data fora similar material)

Respiratory Sensitisation
Not expected to be a respiratory sensitiser.

Skin Sensitisation
Not expected to be a skin sensitiser.

Xylene: Not a sensitiser

Nonane: Not a sensitiser

Germ Cell Mutagenicity
Not considered to be a mutagenic hazard.

Carcinogenicity
Not considered to be a carcinogenic hazard.

Highly refined mineral oil and Xylene are listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity
Not considered to be toxic to reproduction.

STOT - Single Exposure
May cause drowsiness or dizziness.

Xylene: May cause respiratory irritation. May cause drowsiness or dizziness.

Nonane: May cause drowsiness or dizziness.

STOT - Repeated Exposure
May cause damage to organs through prolonged or repeated exposure.

Xylene:
May cause damage to organs through prolonged or repeated
exposure. (Auditory system)

Aspiration Hazard
May be fatal if swallowed and enters airways.

Other Information
This product contains an Ototoxic substance.
Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 12 - Ecological Information

Ecotoxicity
No ecological data available for this material. The available ecological data for the ingredients is given below:

Persistence and degradability
Xylene
Readily biodegradable
Biodegradation: >69%
Octanol Water Partition Coefficient: log Pow: 3.2

Nonane:
Readily biodegradable. (15 d)
Biodegradation 67 - 100 %
Octanol Water Partition Coefficient: log Pow: 5.65

Mobility
Not available

Bioaccumulative Potential
Not available

Other Adverse Effects
Not available

Environmental Protection
Do not discharge this material into waterways, drains and sewers.

Acute Toxicity - Fish
Petroleum distillates/Naphtha
LL50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l/96h
Test Type: semistatic test. Method: OECD Test Guideline 203

Acute Toxicity - Daphnia
Petroleum distillates/Naphtha
EL50 (Daphnia magna (Water flea)): 1.4 mg/l/48h
Test Type: static test. Analytical monitoring: yes
Method: OECD Test Guideline 202. GLP: yes

Hazardous to the Ozone Layer
This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal Considerations
Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. To minimise personal exposure, refer to Section 8 - Exposure Controls and Personal Protection.

Section 14 - Transport Information

Transport Information
Road and Rail Transport (ADG Code):
This material is classified as Dangerous Goods Class 3 - Flammable Liquid
Must not be loaded in the same freight container or on the same vehicle with:
- Class 1: Explosives
- Division 2.1: Flammable gases
- Division 2.3: Toxic gases
- Division 4.2: Spontaneously combustible substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic peroxides or
- Class 7: Radioactive materials unless specifically exempted.

Must not be loaded with in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:
- Division 4.3: Dangerous when wet substances

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:
- Division 4.2: Spontaneously combustible substances
- Division 4.3: Dangerous when wet substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic peroxides

Marine Transport (IMO/IMDG):
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
Class/Division: 3
UN No: 1263
Proper Shipping Name: PAINT RELATED MATERIAL
Packing Group: III
EMS: F-E, S-E
Special Provisions: 163, 367

Air Transport (ICAO/IATA):
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
Class/Division: 3
UN No: 1263
Proper Shipping Name: Paint related material
Packing Group: III
Packaging Instructions (passenger & cargo): 355
Packaging Instructions (cargo only): 366
Hazard Label: Flammable liquid
Special Provisions: A3, A72, A192

UN Number
1263

Proper Shipping Name
PAINT RELATED MATERIAL

Transport Hazard Class
3

Packing Group
III

Hazchem Code
•3Y

IERG Number
14

Special Precautions for User
Not available

IMDG Marine pollutant
Yes

Transport in Bulk
Not available

Section 15 - Regulatory Information

Regulatory Information
Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.
Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule
S5

Montreal Protocol
Not listed

Stockholm Convention
Not listed

Rotterdam Convention
Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL)
Not available

Agricultural and Veterinary Chemicals Act 1994
Not available

Basel Convention
Not listed

Section 16 - Any Other Relevant Information

Date of Preparation
SDS Amendment: November 2026
Section 8 - Exposure Controls and Personal Protection - Occupational exposure limit values

SDS Created: February 2024

Version Number
1.1

Literature References
Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
Standard for the Uniform Scheduling of Medicines and Poisons.
Australian Code for the Transport of Dangerous Goods by Road & Rail.
Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
Code of Practice for Supply Diversion into Illicit Drug Manufacture.
National Code of Practice for Chemicals of Security Concern.
Agricultural Compounds and Veterinary Chemicals Act.
International Agency for Research on Cancer (IARC) Monographs.
Montreal Protocol on Substances that Deplete the Ozone Layer.
Stockholm Convention on Persistent Organic Pollutants (POPs).
Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.
Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.
International Air Transport Association (IATA) Dangerous Goods Regulations.
International Maritime Dangerous Goods (IMDG) Code.
Workplace exposure limits for airborne contaminants.
Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).
Globally Harmonised System of Classification and Labelling of Chemicals (7th revised edition).
Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.
Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.
The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.
Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.